

**Reference: C3673**

## X-Line-1 C3673



<b>Lenght (mm)</b>	1200
<b>Width (mm)</b>	90
<b>Height (mm)</b>	49
<b>System power (W)</b>	28w/35w/36w/40w
<b>Luminous flow (lm)</b>	4480lm/5600lm/5760lm/6400lm
<b>Voltage</b>	220 - 240VAC
<b>Degree of protection</b>	I
<b>Driver lifetime (h)</b>	50'000
<b>Beam angle</b>	90°
<b>Finishing</b>	Black
<b>Light source</b>	SMD
<b>MacAdam</b>	<3
<b>IRC</b>	80Ra
<b>Diffuser</b>	Optique
<b>Fixation</b>	Quart de tour
<b>CDL type</b>	Direct
<b>Connection</b>	Rail Global 6 conducteurs triphasé
<b>Driver output voltage</b>	55-80V
<b>Protection class</b>	I
<b>Matter</b>	Acier
<b>Warranty</b>	5ans
<b>Color temperature</b>	6500K
<b>Light regulation</b>	Dali
<b>Operating temperature</b>	-25° +60°C

Sous réserve de modifications techniques car nos produits sont constamment améliorés.  
We reserve the right to make technical changes as our products are constantly being improved.  
Wir behalten uns das Recht vor, technische Änderungen vorzunehmen, da unsere Produkte ständig verbessert werden.