

Reference: D32070

## Dipper SMD 110 D32070



|                                |                          |
|--------------------------------|--------------------------|
| <b>Diameter (mm)</b>           | Φ110                     |
| <b>Embedding diameter (mm)</b> | Φ100                     |
| <b>Embedding depth (mm)</b>    | 76                       |
| <b>System power (W)</b>        | 13W                      |
| <b>Luminous flow (lm)</b>      | 1014lm                   |
| <b>Voltage</b>                 | AC 220 - 240V            |
| <b>Degree of protection</b>    | IP54                     |
| <b>Luminaire life (h)</b>      | 50000                    |
| <b>Driver lifetime (h)</b>     | 50000                    |
| <b>Beam angle</b>              | 60°                      |
| <b>Finishing</b>               | Blanc (noir sur demande) |
| <b>Light source</b>            | SMD                      |
| <b>UGR</b>                     | < 19                     |
| <b>MacAdam</b>                 | SDCM <3                  |
| <b>IRC</b>                     | >80 (>90 sur demande)    |
| <b>Fixation</b>                | Encastré                 |
| <b>CDL type</b>                | Direct                   |
| <b>Protection class</b>        | Classe II                |
| <b>Matter</b>                  | Aluminium                |
| <b>Warranty</b>                | 5ans                     |
| <b>Color temperature</b>       | 2700K                    |
| <b>Light regulation</b>        | On / Off                 |
| <b>Operating temperature</b>   | -20° + ~40°C             |
| <b>Efficiency</b>              | 78lm/W                   |
| <b>Reflector</b>               | Blanc mat                |