

**Reference: D32793**

## Dipper COB 190



<b>Diameter (mm)</b>	Φ186
<b>Embedding diameter (mm)</b>	Φ175
<b>Embedding depth (mm)</b>	122
<b>System power (W)</b>	35W
<b>Luminous flow (lm)</b>	3360lm
<b>Voltage</b>	AC 220 - 240V
<b>Degree of protection</b>	IP54
<b>Luminaire life (h)</b>	50000
<b>Driver lifetime (h)</b>	50000
<b>Beam angle</b>	50°
<b>Finishing</b>	Blanc (noir sur demande)
<b>Light source</b>	COB
<b>UGR</b>	<19
<b>MacAdam</b>	SDCM <3
<b>IRC</b>	>80 (>90 sur demande)
<b>Fixation</b>	Encastré
<b>CDL type</b>	Direct
<b>Protection class</b>	Classe II
<b>Matter</b>	Aluminium
<b>Warranty</b>	5ans
<b>Color temperature</b>	5000K
<b>Light regulation</b>	On/Off
<b>Operating temperature</b>	-20° + ~40°C
<b>Efficiency</b>	96lm/W
<b>Reflector</b>	Chromé

Sous réserve de modifications techniques car nos produits sont constamment améliorés.  
We reserve the right to make technical changes as our products are constantly being improved.  
Wir behalten uns das Recht vor, technische Änderungen vorzunehmen, da unsere Produkte ständig verbessert werden.