

Reference: D44134

## Kulo B trimless 15W D44134



<b>Diameter (mm)</b>	Ø72
<b>Embedding diameter (mm)</b>	Ø80
<b>Embedding depth (mm)</b>	105
<b>System power (W)</b>	15W
<b>Luminous flow (lm)</b>	1250lm
<b>Voltage</b>	220 - 240V AC 50/60Hz
<b>Degree of protection</b>	IP65 partie visible IP44 encastré
<b>Luminaire life (h)</b>	50'000
<b>Driver lifetime (h)</b>	50'000
<b>Beam angle</b>	25°
<b>Finishing</b>	White
<b>Light source</b>	Direct
<b>UGR</b>	<13
<b>MacAdam</b>	<3
<b>IRC</b>	>90
<b>Fixation</b>	Encastré
<b>CDL type</b>	Direct
<b>Protection class</b>	Classe II
<b>Matter</b>	Aluminium moulé sous pression
<b>Warranty</b>	5 years
<b>Color temperature</b>	3000K
<b>Light regulation</b>	On / Off
<b>Operating temperature</b>	-20 +40°C
<b>Orientation</b>	Oui
<b>Efficiency</b>	83lm/W
<b>Reflector</b>	Nickelé noir

Flicker

Sans scintillement