

Reference: D41411

## Kulo A 12W D41411



|                         |                                   |
|-------------------------|-----------------------------------|
| Diameter (mm)           | Ø82                               |
| Embedding diameter (mm) | Ø75                               |
| Embedding depth (mm)    | 105                               |
| System power (W)        | 12W                               |
| Luminous flow (lm)      | 1150lm                            |
| Voltage                 | 220 - 240V AC 50/60Hz             |
| Degree of protection    | IP65 partie visible IP44 encastré |
| Luminaire life (h)      | 50'000                            |
| Driver lifetime (h)     | 50'000                            |
| Beam angle              | Lèche mur asymetrique             |
| Finishing               | White                             |
| Light source            | Direct                            |
| UGR                     | <13                               |
| MacAdam                 | <3                                |
| IRC                     | >90                               |
| Fixation                | Encastré                          |
| CDL type                | Direct                            |
| Protection class        | Classe II                         |
| Matter                  | Aluminium moulé sous pression     |
| Warranty                | 5 years                           |
| Color temperature       | 3000K                             |
| Light regulation        | On / Off                          |
| Operating temperature   | -20 +40°C                         |
| Orientation             | Non                               |
| Efficiency              | 95lm/W                            |
| Reflector               | Blanc mat                         |

Sous réserve de modifications techniques car nos produits sont constamment améliorés.  
We reserve the right to make technical changes as our products are constantly being improved.  
Wir behalten uns das Recht vor, technische Änderungen vorzunehmen, da unsere Produkte ständig verbessert werden.

Flicker

Sans scintillement