

**Reference: F8492**

## BubblyB T800 F8492



<b>Height (mm)</b>	79
<b>Diameter (mm)</b>	Ø800
<b>System power (W)</b>	47 - 75W
<b>Luminous flow (lm)</b>	7400lm
<b>Voltage</b>	220 - 240V AC
<b>Degree of protection</b>	IP40
<b>Luminaire life (h)</b>	50'000
<b>Driver lifetime (h)</b>	50'000
<b>Beam angle</b>	120°
<b>Finishing</b>	Black
<b>Light source</b>	SMD
<b>IRC</b>	>80
<b>Diffuser</b>	Opal
<b>Fixation</b>	Suspension tube
<b>CDL type</b>	Direct / Indirect
<b>Protection class</b>	Classe I
<b>Matter</b>	Aluminium
<b>Warranty</b>	5ans
<b>Color temperature</b>	4000K
<b>Light regulation</b>	On / Off
<b>Operating temperature</b>	-20°C +40°C
<b>Efficiency</b>	99lm/W
<b>Notes</b>	Éclairage direct
<b>Flicker</b>	Sans scintillement
<b>Weight</b>	3,2Kg

Sous réserve de modifications techniques car nos produits sont constamment améliorés.  
We reserve the right to make technical changes as our products are constantly being improved.  
Wir behalten uns das Recht vor, technische Änderungen vorzunehmen, da unsere Produkte ständig verbessert werden.