


**Reference: F7109**

## Sloop 400 F7109



<b>Height (mm)</b>	62.8
<b>Diameter (mm)</b>	Ø400
<b>System power (W)</b>	25W
<b>Luminous flow (lm)</b>	2400lm
<b>Voltage</b>	220-240V AC
<b>Degree of protection</b>	IP40
<b>Luminaire life (h)</b>	50'000
<b>Driver lifetime (h)</b>	50'000
<b>Beam angle</b>	120°
<b>Finishing</b>	White
<b>Light source</b>	SMD LED
<b>IK resistance</b>	IK08
<b>IRC</b>	>80
<b>Diffuser</b>	Opal
<b>Fixation</b>	Applique
<b>CDL type</b>	Direct
<b>Protection class</b>	Classe II
<b>Matter</b>	PC
<b>Warranty</b>	5ans
<b>Color temperature</b>	4000K
<b>Light regulation</b>	On / Off
<b>Operating temperature</b>	-20°C ~45°C
<b>Orientation</b>	Non
<b>Efficiency</b>	~95lm/W
<b>Flicker</b>	Sans scintillement
<b>Weight</b>	1,75Kg

Sous réserve de modifications techniques car nos produits sont constamment améliorés.  
We reserve the right to make technical changes as our products are constantly being improved.  
Wir behalten uns das Recht vor, technische Änderungen vorzunehmen, da unsere Produkte ständig verbessert werden.