

**Reference: S1802**

## SquareGlow 220 S1802



<b>Lenght (mm)</b>	220
<b>Width (mm)</b>	220
<b>Height (mm)</b>	48
<b>System power (W)</b>	12W
<b>Luminous flow (lm)</b>	1320lm
<b>Voltage</b>	220 - 240V AC
<b>Degree of protection</b>	IP54
<b>Luminaire life (h)</b>	50000
<b>Driver lifetime (h)</b>	50000
<b>Beam angle</b>	120°
<b>Finishing</b>	White
<b>Light source</b>	SMD
<b>IK resistance</b>	IK10
<b>IRC</b>	85
<b>Diffuser</b>	Opal
<b>Fixation</b>	Applique
<b>CDL type</b>	Direct
<b>Matter</b>	PC
<b>Warranty</b>	5ans
<b>Color temperature</b>	3000K
<b>Light regulation</b>	On/Off
<b>Operating temperature</b>	-40 +50°C
<b>Orientation</b>	Non
<b>Efficiency</b>	110lm/W
<b>Notes</b>	Éclairage de secours sur demande
<b>Flicker</b>	Sans scintillement

Sous réserve de modifications techniques car nos produits sont constamment améliorés.  
We reserve the right to make technical changes as our products are constantly being improved.  
Wir behalten uns das Recht vor, technische Änderungen vorzunehmen, da unsere Produkte ständig verbessert werden.

Weight

0,45Kg