

**Reference: D20130**

## HALO9T D20130



|                           |                |
|---------------------------|----------------|
| Lenght (mm)               | 125            |
| Width (mm)                | 125            |
| Depth (mm)                | 35             |
| Largeur encastrément (mm) | 127            |
| Embedding depth (mm)      | 127            |
| System power (W)          | 18W            |
| Luminous flow (lm)        | 1900lm         |
| Voltage                   | 200-240V AC    |
| Degree of protection      | IP20           |
| Luminaire life (h)        | 50'000H        |
| Driver lifetime (h)       | 50'000H        |
| Beam angle                | 35°            |
| Finishing                 | Argent RAL9006 |
| Light source              | LED 3535       |
| UGR                       | 14             |
| MacAdam                   | 3              |
| IRC                       | 80             |
| Diffuser                  | PC             |
| Fixation                  | Trimless       |
| CDL type                  | Direct         |
| Driver brand              | Osram          |
| Driver output amperage    | 600mA          |
| Driver output voltage     | 23-42V         |
| Protection class          | Class II       |
| Matter                    |                |
| Warranty                  | 5 years        |

Sous réserve de modifications techniques car nos produits sont constamment améliorés.  
We reserve the right to make technical changes as our products are constantly being improved.  
Wir behalten uns das Recht vor, technische Änderungen vorzunehmen, da unsere Produkte ständig verbessert werden.

|                       |             |
|-----------------------|-------------|
| Color temperature     | 4000K       |
| Light regulation      | On-off      |
| Operating temperature | -20°C ~40°C |

