

Reference: D20447

HALO9A D20447



Lenght (mm)	128
Width (mm)	128
Depth (mm)	88
System power (W)	18W
Luminous flow (lm)	1900lm
Voltage	200-240V AC
Degree of protection	IP20
Luminaire life (h)	50'000H
Driver lifetime (h)	50'000H
Beam angle	65°
Finishing	Argent RAL9006
Light source	LED 3535
UGR	17
MacAdam	3
IRC	80
Diffuser	PC
Fixation	Applique
CDL type	Direct
Driver brand	BOKE
Driver output amperage	600mA
Driver output voltage	25-42V
Protection class	Class II
Matter	
Warranty	5 years
Color temperature	3000K
Light regulation	On-off

Sous réserve de modifications techniques car nos produits sont constamment améliorés.
We reserve the right to make technical changes as our products are constantly being improved.
Wir behalten uns das Recht vor, technische Änderungen vorzunehmen, da unsere Produkte ständig verbessert werden.

Operating temperature

-20°C ~40°C



Sous réserve de modifications techniques car nos produits sont constamment améliorés.
We reserve the right to make technical changes as our products are constantly being improved.
Wir behalten uns das Recht vor, technische Änderungen vorzunehmen, da unsere Produkte ständig verbessert werden.